United States Patent [19]

Taniguchi et al.

[11] Patent Number: **5,635,317**

[45] **Date of Patent:** **Jun. 3, 1997**

[54] **PREPARATION AND REPRODUCTION OF FILTERS AND PREPARATION OF FILTER PHOTOGRAPHIC MATERIALS**

[75] Inventors: **Yukio Taniguchi; Minoru Utsumi,** both of Tokyo, Japan

[73] Assignee: **Dai Nippon Printing Co., Ltd.,** Tokyo, Japan

[21] Appl. No.: **416,182**

[22] Filed: **Apr. 4, 1995**

Related U.S. Application Data

[62] Division of Ser. No. 613,684, Nov. 15, 1990.

[30] **Foreign Application Priority Data**

Mar. 16, 1989	[JP]	Japan	....	1-64259
Mar. 16, 1989	[JP]	Japan	....	1-64260
Mar. 18, 1989	[JP]	Japan	....	1-67250

[51] **Int. Cl.^{6}** **G03F 9/00**

[52] **U.S. Cl.** **430/7**; 430/20; 430/256

[58] **Field of Search** 430/7, 20, 27, 430/329, 383, 357, 356, 127

[56] **References Cited**

U.S. PATENT DOCUMENTS

T861,026	4/1969	Harper et al. .
3,506,327	4/1970	Leith et al. .
3,567,305	3/1971	Collier et al. .
3,633,989	1/1972	Benton .
3,647,289	3/1972	Weber .
3,758,186	9/1973	Brumm .
3,776,727	12/1973	Nassenstein et al. .
4,071,291	1/1978	Suzuki et al. .
4,171,766	10/1979	Ruell .
4,244,633	1/1981	Kellie .
4,370,936	2/1983	Sato et al. 430/7
4,719,160	1/1988	Gerhart et al. .
4,778,262	10/1988	Haines .
4,788,116	11/1988	Hochberg .
4,877,697	10/1989	Vollmann et al. 430/20
4,889,780	12/1989	Cosner .
4,958,892	9/1990	Jannson et al. .

FOREIGN PATENT DOCUMENTS

47-26753	10/1972	Japan .
53-36335	10/1978	Japan .
56-4108	1/1981	Japan .
57-8213	7/1982	Japan .
63-47131	3/1988	Japan .

OTHER PUBLICATIONS

Born & Wolf "Principles of Optics" 1970; p. 280; Fourth Edition; Pergmon Press.

Primary Examiner—Thorl Chea
Attorney, Agent, or Firm—Armstrong, Westerman, Hattori, McLeland & Naughton

[57] **ABSTRACT**

A filter photographic material is produced by laminating together, in opposite relation, a first laminate obtained by laminating a filter layer and an adhesive layer successively on a support and a second laminate obtained by laminating a photoconductive layer and a transparent electrode layer successively on a carrier film through a release layer, followed by removal of the carrier film. Thus, it is possible to prevent the discoloration, fading, etc. of the filter layer and its preparation is made more efficient.

2 Claims, 6 Drawing Sheets